

SHORT SMOCK (VCC) NYLPECHE

CE R

Technical data

PROTECTION FRAMEWORK EN 343: 2019

This garment is designed to protect from bad weather, precipitations in the form of rain or snow, fog, spray and moisture on the ground.

<u>For professional use</u>: **Fishing - agriculture - industry - cleaning** or other activities requiring this kind of protection.

THIS ARTICLE IS A

CATEGORY 1 PPE

And complies with EU regulation 2016/425

PPE = Personal Protective Equipment

PERFORMANCE



The assembled parts are High Frequency welded, guaranteeing a waterproof garment.

- Water penetration resistance ≥ 20,000 Pa = Class 4
- Evaporative resistance = n/a
 Ret > 40 m².Pa/W = Class 1

RESTRICTIONS ON USE

(specified in the EN 343: 2019 standard)

"A maximum continuous wear time is recommended for 1 full suit (jacket + trousers) without a thermal lining"

Ambient work	Time
temperature in °C	in minutes
25	60
20	75
15	100
10	240
5	Unlimited

ILLUSTRATION AND INSTRUCTIONS



For maximum protection, the VCC short smock can be worn with PPE classed trousers or bib & braces.

PRINCIPAL MATERIALS

Nylpêche fabric - 485 g/m²

Composition: 69 % PVC - 31 % Polyester

Double-sided coating

Features:

- WATERPROOF
- HEAVY DUTY

INSTRUCTIONS

CARE



- STORAGE
- Do not leave in package in damp surroundings.
- Store in dry surroundings at room temperature.
- Keep away from strong heat and flames.

SIZE TABLE

Size	Size of the person's body (in cm)		Guideline measurements of clothing (in cm)	
	Stature	Chest size	Chest size	
S	165-170	86-94	136	
M	170-180	94-102	144	<u>Colour</u> : yellow
L	175-185	102-110	154	Sizes: S – M – L – XL – XXL
XL	180-190	110-124	168	312E3. 3 - IVI - L - AL - AAL
XXL	185+	124-134	178	

The lifespan of the garment is linked to conditions of use and the quality of its care.