

ETAL APRON NYLPECHE

Technical data

THIS ARTICLE IS A

CATEGORY | PPE

And complies with EU regulation 2016/425

PPE = Personal Protective Equipment

Back

PROTECTION FRAMEWORK / EN 343: 2003 + A1: 2007

This garment is designed to protect from bad weather, precipitations in the form of rain or snow, fog, spray and moisture on the ground.

For professional use: Fishing - agriculture - industry - cleaning or other activities requiring this kind of protection.

PERFORMANCE

Restricted wear time

The assembled parts are High Frequency welded, guaranteeing a waterproof garment.

- Water penetration resistance ≥ 13.000 Pa = Class 3
- Evaporative resistance = n/a Ret > 40 m².Pa/W = Class 1

RESTRICTIONS ON USE

(specified in the EN 343: 2007 standard) "A maximum continuous wear time is recommended for 1 full suit (jacket + trousers) without a thermal lining"

Ambient work	Time
temperature in °C	In minutes
25	60
20	75
15	100
10	240
5	Unlimited

PRINCIPAL MATERIALS

Nylpêche fabric - 485 g/m² Composition: 69 % PVC - 31 % Polyester Double-sided coating + polyethylene foam inside the reinforcement

Features:

- WATERPROOF
- HEAVY DUTY

INSTRUCTIONS



STORAGE

- Do not leave in package in damp surroundings.

- Store in dry surroundings at room temperature.

- Keep away from strong heat and flames.



For maximum protection, the ETAL apron can be worn with oversleeves, gloves and PPE classed wellington boots.

SIZE TABLE

	Size of the person's body (in cm)		Guideline measurements of clothing (in cm)				
Size	Stature	Waist size	Chest size	Waist size	Bib protection width	Apron length	
S	165-170	76-84	86-94	95 - 125 (adjustment strap)	30	100	
М	170-180	84-92	94-102	95 - 125 (adjustment strap)	30	107	<u>Col</u>
L	175-185	92-100	102-110	95 - 125 (adjustment strap)	30	115	<u>Size</u>

white, blue

– M – L

The lifespan of the garment is linked to conditions of use and the quality of its care.