

ISOCONF APRON NYLPECHE

CE RR

Technical data

PROTECTION FRAMEWORK EN 343: 2019

This garment is designed to protect from bad weather, precipitations in the form of rain or snow, fog, spray and moisture on the ground.

<u>For professional use</u>: **Fishing - agriculture - industry - cleaning** or other activities requiring this kind of protection.

THIS ARTICLE IS A

CATEGORY 1 PPE

And complies with EU regulation 2016/425

PPE = Personal Protective Equipment



The assembled parts are High Frequency welded, guaranteeing a waterproof garment.

- Water penetration resistance
 ≥ 20,000 Pa = Class 4
- Evaporative resistance = n/a Ret > 40 m².Pa/W = **Class 1**

RESTRICTIONS ON USE

(specified in the EN 343: 2019 standard)

"A maximum continuous wear time is recommended for 1 full suit (jacket + trousers) without a thermal lining"

| Ambient work temperature in °C | Time in minutes | |
|--------------------------------|--------------------|--|
| 25 | 60 | |
| 20 | 75 | |
| 15 | 100 | |
| 10 | 240 | |
| 5 | Unlimited | |



PRINCIPAL MATERIALS

Nylpêche fabric - 485 g/m²

Composition: 69 % PVC - 31 % Polyester

Double-sided coating

+ polyethylene foam inside the reinforcement

Features:

- WATERPROOF
- HEAVY DUTY

INSTRUCTIONS

CARE



- STORAGE
- Do not leave in package in damp surroundings.
- Store in dry surroundings at room temperature.
- Keep away from strong heat and flames.

For maximum protection, the ISOCONF apron with can be worn with oversleeves, gloves and PPE classed wellington boots.

SIZE TABLE

| Size | Size of the person's body (in cm) | | Guideline measurements of clothing (in cm) | | | |
|-------------|-----------------------------------|---------------|--|---|----------------------------|-----------------|
| | Stature | Waist size | Chest size | Waist size | Bib protection width | Apron length |
| One size | 150-185+ | 60-116+ | 78-134+ | 119 (elastic unstretched) 129 (elastic stretched) | 35 | 128 |



<u>Colour</u>: blue, blue/yellow

Tailles: one size

The lifespan of the garment is linked to conditions of use and the quality of its care.