

CHINOOK SMOCK GLENTEX

C€ R

Technical data

PROTECTION FRAMEWORK EN 343: 2019

This garment is designed to protect from bad weather, precipitations in the form of rain or snow, fog, spray and moisture on the ground.

<u>For professional use</u>: **Fishing - agriculture - industry - cleaning** or other activities requiring this kind of protection.


THIS ARTICLE IS A

CATEGORY 1 PPE

And complies with EU regulation 2016/425

PPE = Personal Protective Equipment

PERFORMANCE



The assembled parts are High Frequency welded, guaranteeing a waterproof garment.

- Water penetration resistance ≥ 20,000 Pa = Class 4
- Evaporative resistance = n/a
 Ret > 40 m².Pa/W= Class 1

RESTRICTIONS ON USE

(specified in the EN 343: 2019 standard)

"A maximum continuous wear time is recommended for 1 full suit (jacket + trousers) without a thermal lining"

Ambient work	Time	
temperature in °C	in minutes	
25	60	
20	75	
15	100	
10	240	
5	Unlimited	

ILLUSTRATION AND INSTRUCTIONS



For maximum protection, the CHINOOK smock can be worn with PPE classed trousers or bib & braces.

PRINCIPAL MATERIALS

Glentex fabric - 320 g/m²

Composition: 80 % PVC – 20 % Polyester Coated on one side

Features:

- COMFORTABLE
- WATERPROOF
- LIGHT

INSTRUCTIONS

CARE



- STORAGE
- Do not leave in package in damp surroundings.
- Store in dry surroundings at room temperature.
- Keep away from strong heat and flames.

SIZE TABLE

Size	Size of the person's body (in cm)		Guideline measurements of clothing (in cm)	Colour: fluorescent
	Stature	Chest size	Chart size	orange/black, grey/black, dark
S	165-170	86-94	122	yellow/ black <u>Sizes</u> : S – M – L – XL – XXL – PLUS SIZE (dark yellow/black;
М	170-180	94-102		
L	175-185	102-110		
XL	180-190	110-124	156	grey/black)
XXL	185+	124-134	168	

The lifespan of the garment is linked to conditions of use and the quality of its care.