

PRAIRIE COAT PV SOFT

CE R

Technical data

PROTECTION FRAMEWORK EN 343: 2019

This garment is designed to protect from bad weather, precipitations in the form of rain or snow, fog, spray and moisture on the ground.

Pockets under

Snap-fastening elasticated cuffs.

flap

<u>For professional use</u>: **Fishing - agriculture - industry - cleaning** or other activities requiring this kind of protection.


THIS ARTICLE IS A

CATEGORY | PPE

And complies with EU regulation 2016/425

PPE = Personal Protective Equipment

PERFORMANCE



The assembled parts are High Frequency welded, guaranteeing a waterproof garment.

- Water penetration resistance
 ≥ 20,000 Pa = Class 4
- Evaporative resistance = n/a
 Ret > 40 m².Pa/W = Class 1

RESTRICTIONS ON USE

(specified in the EN 343: 2019 standard)

"A maximum continuous wear time is recommended for 1 full suit (jacket + trousers) without a thermal lining"

Ambient work	Time
temperature in °C	In minutes
25	60
20	75
15	100
10	240
5	Unlimited

ILLUSTRATION AND INSTRUCTIONS

Roll away hood in 2 sections in collar, with drawstring.



Zip under snapfastening double flap

Coat length extends

to cover top of boots

PRINCIPAL MATERIALS

PV Soft fabric - 265 g/m²

Composition: 82 % PVC – 18 % Polyester

Coated on one side

Features:


- LIGHT
- WATERPROOF
- EFFECTIVE

INSTRUCTIONS

CARE



- STORAGE
- Do not leave in package in damp surroundings.
- Store in dry surroundings at room temperature.
- Keep away from strong heat and flames.



SIZE TABLE

Size of t		person's body n cm)	Guideline measurements of clothing (in cm)
	Stature	Chest size	Chest size
XS	150-165	78-86	134
S	165-170	86-94	134
M	170-180	94-102	134
L	175-185	102-110	138
XL	180-190	110-124	144
XXL	185+	124-134	148

Colour: green

<u>Sizes</u>: XS – S - M - L - XL - XXL

The lifespan of the garment is linked to conditions of use, storage and the quality of its care.