

VAL JACKET PV SOFT

CE LK Technical data

PROTECTION FRAMEWORK EN 343: 2019

This garment is designed to protect from bad weather, precipitations in the form of rain or snow, fog, spray and moisture on the ground.

For professional use: Fishing - agriculture - industry - cleaning or other activities requiring this kind of protection.

PERFORMANCE

The assembled parts are High Frequency welded, guaranteeing a waterproof garment.

- Water penetration resistance
 ≥ 20,000 Pa = Class 4
- Evaporative resistance = n/a Ret > 40 m².Pa/W = Class 1

RESTRICTIONS ON USE

(specified in the EN 343: 2019 standard) "A maximum continuous wear time is recommended for 1 full suit (jacket + trousers) without a thermal lining"

Ambient work	Time	
temperature in °C	in minutes	
25	60	
20	75	
15	100	
10	240	
5	Unlimited	

PRINCIPAL MATERIALS

PV Soft fabric - 265 g/m² Composition: 82 % PVC – 18 % Polyester Coated on one side

Features:

- WATERPROOF
- LIGHT

INSTRUCTIONS



STORAGE
Do not leave in package in damp

surroundings.

- Store in dry surroundings at room temperature.

- Keep away from strong heat and flames.



CATEGORY **1** PPE

And complies with EU regulation 2016/425 PPE = Personal Protective Equipment

ILLUSTRATION AND INSTRUCTIONS



For maximum protection, the VAL jacket can be worn with PPE classed trousers or bib & braces.

SIZE TABLE

Size		e person's body in cm)	Guideline measurements of clothing (in cm)	
	Stature	Chest size	Chest size	
XS	150-165	78-86	132	
S	165-170	86-94	132	
М	170-180	94-102	132	<u>Colour</u> : green
L	175-185	102-110	136	
XL	180-190	110-124	142	<u>Sizes</u> : XS - S – M – L – XL
XXL	185+	124-134	148	– XXL

The lifespan of the garment is linked to conditions of use and the quality of its care.

Declaration of conformity on www.guycotten.com