

PROTECTION FRAMEWORK / EN 343: 2003 + A1: 2007

This garment is designed to protect from bad weather, precipitations in the form of rain or snow, fog, spray and moisture on the ground.

For professional use: Fishing - agriculture - industry - cleaning or other activities requiring this kind of protection.

PERFORMANCE


1 Restricted wear time

The assembled parts are High Frequency welded, guaranteeing a waterproof garment.

- Water penetration resistance $\geq 13,000$ Pa = **Class 3**
- Evaporative resistance = n/a
Ret > 40 m².Pa/W = **Class 1**

RESTRICTIONS ON USE

(specified in the EN 343: 2007 standard)

"A maximum continuous wear time is recommended for 1 full suit (jacket + trousers) without a thermal lining"

| Ambient work temperature in °C | Time in minutes |
|--------------------------------|-----------------|
| 25 | 60 |
| 20 | 75 |
| 15 | 100 |
| 10 | 240 |
| 5 | Unlimited |

PRINCIPAL MATERIALS

PV Soft fabric - 265 g/m²

Composition: 89 % PVC – 11 % Polyester
Coated on one side

Features:

- **WATERPROOF**
- **LIGHT**

INSTRUCTIONS

- CARE



- STORAGE

- Do not leave in package in damp surroundings.
- Store in dry surroundings at room temperature.
- Keep away from strong heat and flames.

ILLUSTRATION AND INSTRUCTIONS


i For maximum protection, the VAL jacket can be worn with PPE classed trousers or bib & braces.

SIZE TABLE

| Size | Size of the person's body (in cm) | | Guideline measurements of clothing (in cm) |
|------|-----------------------------------|------------|--|
| | Stature | Chest size | Chest size |
| XS | 150-165 | 78-86 | 132 |
| S | 165-170 | 86-94 | 132 |
| M | 170-180 | 94-102 | 132 |
| L | 175-185 | 102-110 | 136 |
| XL | 180-190 | 110-124 | 142 |
| XXL | 185+ | 124-134 | 148 |



Colour: green

Sizes: XS - S - M - L - XL - XXL

The lifespan of the garment is linked to conditions of use and the quality of its care.