



### PROTECTION FRAMEWORK / EN 343: 2003 + A1: 2007

This garment is designed to protect from bad weather, precipitations in the form of rain or snow, fog, spray and moisture on the ground.

For professional use: Fishing - agriculture - industry - cleaning or other activities requiring this kind of protection.

### PERFORMANCE



1 Restricted wear time

The assembled parts are High Frequency welded, guaranteeing a waterproof garment.

- Water penetration resistance  $\geq 13,000 \text{ Pa} = \text{Class 3}$
- Evaporative resistance = n/a  
Ret  $> 40 \text{ m}^2 \cdot \text{Pa} / \text{W} = \text{Class 1}$

### RESTRICTIONS ON USE

(specified in the EN 343: 2007 standard)

"A maximum continuous wear time is recommended for 1 full suit (jacket + trousers) without a thermal lining"

Ambient work temperature in °C	Time in minutes
25	60
20	75
15	100
10	240
5	Unlimited

### PRINCIPAL MATERIALS

Rednyl fabric -  $320 \text{ g/m}^2$

Composition: 81 % PVC – 19 % Polyester  
Coated on one side

### Features:

- SUPPLE
- WATERPROOF
- EFFECTIVE

### INSTRUCTIONS

- CARE



- STORAGE

- Do not leave in package in damp surroundings.
- Store in dry surroundings at room temperature.
- Keep away from strong heat and flames.

### ILLUSTRATION AND INSTRUCTIONS



For maximum protection, the PARAFLOTTE jacket can be worn with PPE classed trousers or bib & braces.

### SIZE TABLE

Size	Size of the person's body (in cm)		Guideline measurements of clothing (in cm)
	Stature	Chest size	Chest size
XS	150-165	78-86	138
S	165-170	86-94	144
M	170-180	94-102	152
L	175-185	102-110	158
XL	180-190	110-124	168
XXL	185+	124-134	178



Colour: green, navy

Sizes: XS - S - M - L - XL - XXL

The lifespan of the garment is linked to conditions of use and the quality of its care.