



PROTECTION FRAMEWORK

EN ISO 12402-3: 2006 – Life jackets, performance level 150

A life jacket that will lift an exhausted or unconscious man overboard to the surface as quickly as possible, without affecting his health and turn him in a position that will allow him to breath while waiting to be rescued.

Intended to be worn by all persons exposed by their work to the risk of falling overboard and drowning.

Universal use: for fishing, coastal waters and open seas.

THIS ARTICLE IS A

CATEGORY 3 PPE

And complies with EU regulation 2016/425

PPE = Personal Protective Equipment

PERFORMANCE



Buoyancy of around 170 Newtons

Completely automatic self-inflation

Manual trigger device included

CO2 indicator according to the depth of thread

Content of the gas cartridge = 32 g CO2

Quick and easy pill replacement, cartridge loading and rearming

The buoyancy chamber is covered with a 300-cm² retroreflective strip

Deck harness and crotch strap included

Glentex collar for enhanced comfort



Very short, compact shape, fitting the body perfectly, not impairing movement, comfortable and light

Outer envelope made of Nylpêche fabric for better wear resistance

Easy to slip on with an adjustable plastic clip buckle at the front

Lung with double wall

Manual pull cord trigger and mouthpiece for oral inflation

Fitted with a crotch strap

2 tone whistle

Equipped with a fixation for a multi-flash light or beacon



Option: MANUAL KIT overriding self-inflation

Option: Can be worn under the 3D vest or under the ISOTOP smock

PRINCIPAL MATERIALS

Outer fabric: Nylpêche - 485 g/m²

Composition: 69 % PVC – 31 % Polyester

Outer fabric: Glentex - 320 g/m²

Composition: 80% PVC – 20% Polyester

Polyurethane PVC coating

INSTRUCTIONS

- CARE
 - Regularly use oral inflation to check the life jacket.
- STORAGE
 - - 54°C to + 70°C
 - Never fold it when wet.
 - Before storing, check the jacket is properly rearmed (cf Kit)

i For maximum protection, please check the condition of your life jacket, the trigger devices and its servicing date.

To protect the trigger bobbin/pill from dissolving prematurely due to high temperatures/atmospheric humidity, remember to change the bobbins/pills accordingly.

Annual servicing is a must. Have your jacket serviced by one of the approved GUY COTTEN servicing stations.

A neoprene cuff (sold on option) can be adapted to prevent the buckle catching.

Colour: orange/black

Tailles: one size

Weight of person: 40 to 120 kg

Weight of jacket: about 1.3 kg

The lifespan of your equipment is linked to conditions of use and quality of care