

PROTECTION FRAMEWORK EN 343: 2019

This garment is designed to protect from bad weather, precipitations in the form of rain or snow, fog, spray and moisture on the ground.

For professional use: Fishing - agriculture - industry - cleaning or other activities requiring this kind of protection.

PERFORMANCE  (limited wearing time)

The assembled parts are High Frequency welded, guaranteeing a waterproof garment.

- Water penetration resistance $\geq 20,000$ Pa = **Class 4**
- Evaporative resistance = n/a
Ret > 40 m².Pa/W = **Class 1**

RESTRICTIONS ON USE

(specified in the EN 343: 2019 standard)

“A maximum continuous wear time is recommended for 1 full suit (jacket + trousers) without a thermal lining”

Ambient work temperature in °C	Time in minutes
25	60
20	75
15	100
10	240
5	Unlimited

PRINCIPAL MATERIALS

Fisher fabric - 580 g/m²

Composition: 91 % PVC – 9 % Polyester

Coated on one side

Features:

- **WATERPROOF**
- **TOUGH**

INSTRUCTIONS

- CARE



- STORAGE

- Do not leave in package in damp surroundings.
- Store in dry surroundings at room temperature.
- Keep away from strong heat and flames.

ILLUSTRATION AND INSTRUCTIONS


Heavy duty zip beneath double flap with concealed snap-fasteners.



Adjustable hood with visor



Snap-fastening elasticated cuffs with gusset



 For maximum protection, the GAMVIK FISHER jacket can be worn with PPE classed trousers or bib & braces.

SIZE TABLE

Size	Size of the person's body (in cm)		Guideline measurements of clothing (in cm)
	Stature	Chest size	Chest size
XS	150-165	78-86	136
S	165-170	86-94	144
M	170-180	94-102	148
L	175-185	102-110	156
XL	180-190	110-124	164
XXL	185+	124-134	176



Colour: orange

Sizes: XS – S – M – L – XL
– XXL

The lifespan of the garment is linked to conditions of use and the quality of its care.