




PROTECTION FRAMEWORK EN 343: 2019

This garment is designed to protect from bad weather, precipitations in the form of rain or snow, fog, spray and moisture on the ground.

For professional use: **Fishing - agriculture - industry - cleaning** or other activities requiring this kind of protection.

PERFORMANCE



(limited wearing time)

The assembled parts are High Frequency welded, guaranteeing a waterproof garment.

- Water penetration resistance $\geq 20,000 \text{ Pa} = \text{Class 4}$
- Evaporative resistance = n/a
Ret $> 40 \text{ m}^2 \cdot \text{Pa/W} = \text{Class 1}$

RESTRICTIONS ON USE

(specified in the EN 343: 2019 standard)

"A maximum continuous wear time is recommended for 1 full suit (jacket + trousers) without a thermal lining"

Ambient work temperature in °C	Time in minutes
25	60
20	75
15	100
10	240
5	Unlimited

PRINCIPAL MATERIALS

Nylpêche fabric - 485 g/m^2
 Composition: 76 % PVC – 24 % Polyester
 Double-sided coating
 + polyethylene foam inside the reinforcement

Features:

- **WATERPROOF**
- **HEAVY DUTY**

INSTRUCTIONS

- CARE



- STORAGE

- Do not leave in package in damp surroundings.
- Store in dry surroundings at room temperature.
- Keep away from strong heat and flames.

ILLUSTRATION AND INSTRUCTIONS



Plastic buckle adjustment of over-neck fabric strap

The ISOLATECH technique (patented) used for the stomach reinforcement reduces condensation inside the apron working in a cold environment

Adjustment strap at the waist

Wraparound coverage for better protection



For maximum protection, the ISOFRANC apron with ordinary straps can be worn with cuffs, gloves and PPE classed wellington boots.

SIZE TABLE

Size	Size of the person's body (in cm)		
	Stature	Waist size	Chest size
One size	150-185+	60-116+	78-134+



Colour: white, blue, yellow, green

Size : One size

The lifespan of the garment is linked to conditions of use and the quality of its care.